


Les produits d'éclairage

# AimLite


Lighting Products

**Filename:** R12R-1-LA2-90-30K-F**Manufacturer:** Aimlite lighting**Luminaire:** R12R-L**Luminaire Cat:** R12R-1-L-A2-90-(A-H)-(B-W)-(B-S-W)-(B-S-W)-30K-F**Lamp:** (1) COB VERO18-(BXR-30G4000-C-73-SE) c/w Universal Driver  
D15CC55UNVTW-LS @ 120.00V**Distribution:** Direct Type - Downlight**Lamp Output:** Total luminaire Lumens: 2426.6**Max Candela:** 5,336.0 at Horizontal: 0°, Vertical: 0°**Input Wattage:** 33**Luminous Opening:** Circular (Dia: 2.75")**Test:** S1702172-R1 config from**Test Lab:** Spectra Lux Industries Inc.**Photometry :** Type C**CIE Class:** Direct**Cutoff Class:** Full Cutoff**Nema Type:** 5 X 5**Zonal Lumen Summary**

Zone	Lumens	% Luminaire
0-30	2,011.9	82.9%
0-40	2,387.2	98.4%
0-60	2,426.6	100%
60-90	0	0%
70-100	0	0%
90-120	0	0%
0-90	2,426.6	100%
90-180	0	0%
0-180	2,426.6	100%

**Lumens Per Zone**

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	466.6	19.2%	90-100	0	0%
10-20	907.6	37.4%	100-110	0	0%
20-30	637.7	26.3%	110-120	0	0%
30-40	375.3	15.5%	120-130	0	0%
40-50	39.4	1.6%	130-140	0	0%
50-60	0	0.0%	140-150	0	0%
60-70	0	0.0%	150-160	0	0%
70-80	0	0.0%	160-170	0	0%
80-90	0	0.0%	170-180	0	0%



**Illuminance at a Distance**

	Center Beam fc	Beam Width
1.7ft	1,846 fc	1.1 ft
3.3ft	490 fc	2.1 ft
5.0ft	213 fc	3.2 ft
6.7ft	119 fc	4.3 ft
8.3ft	77.5 fc	5.4 ft
10.0ft	53.4 fc	6.4 ft

■ Beam Spread: 35.7°

**Coefficients Of Utilization - Zonal Cavity Method**

Effective Floor Cavity Reflectance: 20%

RCC %:	80				70				50				30				10				0
RW %:	70	50	30	0	70	50	30	0	50	30	20	10	50	30	20	10	50	30	20	10	0
RCR: 0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.02	1.02	1.02	1.00
1	1.14	1.12	1.10	1.08	1.12	1.10	1.08	.95	1.06	1.04	1.03	1.02	1.01	1.00	.99	.98	.97	.95	.93	.92	.90
2	1.10	1.05	1.02	.99	1.07	1.04	1.00	.91	1.00	.98	.96	.98	.95	.94	.95	.93	.92	.90	.88	.87	.85
3	1.05	.99	.95	.92	1.03	.98	.94	.86	.96	.92	.90	.93	.90	.88	.91	.89	.87	.85	.83	.81	.79
4	1.01	.94	.89	.86	.99	.93	.89	.82	.91	.87	.84	.89	.86	.83	.87	.85	.82	.81	.78	.77	.75
5	.97	.89	.84	.81	.95	.88	.84	.78	.87	.83	.80	.85	.82	.79	.84	.81	.78	.77	.74	.73	.71
6	.93	.85	.80	.76	.91	.84	.79	.74	.83	.79	.75	.82	.78	.75	.80	.77	.74	.73	.70	.69	.67
7	.89	.81	.76	.72	.88	.80	.76	.71	.79	.75	.72	.78	.74	.71	.77	.74	.71	.70	.67	.66	.64
8	.86	.77	.72	.69	.84	.77	.72	.68	.76	.71	.68	.75	.71	.68	.74	.70	.68	.67	.65	.64	.62
9	.82	.74	.69	.65	.81	.74	.69	.65	.73	.68	.65	.72	.68	.65	.71	.67	.65	.64	.62	.61	.60
10	.79	.71	.66	.63	.78	.70	.66	.62	.70	.65	.62	.69	.65	.62	.68	.65	.62	.61	.60	.59	.57

**Luminaire Report Summary**

IESNA:LM-63-2002  
 [ISSUE DATE] 17 February 2017  
 [TEST LAB] Spectra Lux Industries Inc.  
 [TEST] S1702172-R1 config from  
 [MANUFACTURER] Aimlite lighting  
 [LUMINAIRE] R12R-1-L-A2-90-(A-H)-(B-W)-(B-S-W)-(B-S-W)-30K-F  
 [LUMINAIRE] R12R-L  
 [LAMP] (1) COB VERO18-(BXRC-30G4000-C-73-SE) c/w Universal Driver D15CC55UNVTW-LS  
 @ 120.00V  
 [BURNING] Vertical Base Up (2,428 Luminaire Lumens)  
 [REFLECTOR] Specular Spun Aluminum (Flood)  
 [LENS] None  
 [HOUSING] Fabricated Metal Sheet  
 [DISTRIBUTION] Direct Type - Downlight  
  
 FILE: CREATED USING ABSOLUTE PHOTOMETRY  
 FILE: CANDELA MULTIPLIER: 0.58  
 FILE: VERTICAL ANGLES: 67, HORIZONTAL ANGLES: 1  
 FILE: COORDINATE SYSTEM: TYPE C  
 FILE: UNIT OF MEASURE: STANDARD  
 FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.29 copyright 2003-2018 by jSolutions, Inc.  
 Reported data calculated from manufacturer's data file, based on IES recommended methods.