



AimLite

F12 LED FLOOD LIGHT GEN 2

QUICK AND EASY MOUNTING ACCESSORIES (SOLD SEPARATELY)
SELECTABLE COLOR TEMPERATURE (3 000/4 000/5 000 K)¹
POWER SELECTABLE¹



FEATURES

- Power Selectable and 3 CCT Selectable (3 000/4 000/5 000 K)¹
- Single power and single CCT also available
- Universal mountings: wall, ground and pole mounting
- Clear Polycarbonate lens
- NEMA 7Hx6V or 7Hx7V
- 0-10 V dimmable
- 120-277 V and 347-480 V
- Ambient temperature: -40°C to 40°C
- 10 KV surge protection
- Occupancy sensor, 3 pin and 7 pin receptacle optional



¹ AVAILABLE ON SOME CONFIGURATIONS. CONSULT SPEC SHEET FOR MORE DETAILS.

AimLite

F12

T 514 227-1288

TF 1866 348-2374

aimlite.com



100 W
13 127 - 13 889 lm



150 W
20 649 - 21 518 lm



230 W
31 954 - 34 040 lm



300 W
40 569 - 42 098 lm



400 W
57 654 - 58 148 lm



50/80/100/150 W
6 800 - 19 200 lm



150/200/240/300 W
22 400 - 38 000 lm



CCT SELECTABLE SWITCH
3 000/4 000/5 000 K

POWER SELECTABLE SWITCH
50/80/100/150 W or
150/200/240/300 W

MOUNTING ACCESSORIES [ORDER SEPARATELY]

CAS979-YOKE-S-BR
YOKE FOR F12S-F12M



CAS979-YOKE-L-BR
YOKE FOR F12L-F12X



CAS979-SWIVEL-BR
SLIPFITTER



CAS979-PA6-RNDSQBR
SQUARE/ROUND POLE ARM



CAS979-TRUNNION-BR
TRUNNION



KITCAS979-SW-AD-BR
SLIPFITTER AND WALL MOUNT ADAPTER

